



Head office address: 241 Bradwick Drive, Concord, Ontario, Canada L4K 1K5  
 Mailing address: P.O. Box 90, Concord, Ontario, Canada L4K 1B2

Tel: (905) 660-6450 Toll free: 1-800-872-1968 Fax: (905) 660-6435 E-mail: info@dcl-inc.com Website: www.dcl-inc.com



## QUICK-LID® HOUSINGS WITH ANSI FLANGES

Flange Size	DC63/DC73				DC64/DC74						DC64.5/DC74.5					
	6"	8"	10"	12"	8"	10"	12"	14"	16"	18"	8"	10"	12"	14"	16"	18"
L – Length in (mm)	35.1 (892)	30.7 (779)	27.0 (685)	23.5 (597)	37.3 (947)	33.6 (853)	30.2 (768)	27.9 (709)	24.5 (622)	20.2 (512)	42.6 (1081)	38.8 (986)	35.4 (898)	33.1 (841)	29.6 (753)	26.2 (666)
W – Width in (mm)	24.9 (632)	24.9 (632)	24.9 (632)	24.9 (632)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)
H – Height in (mm)	25.3 (642)	25.3 (642)	25.3 (642)	25.3 (642)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)

Flange Size	DC65/DC75								DC66/DC76							
	8"	10"	12"	14"	16"	18"	20"	22"	10"	12"	14"	16"	18"	20"	22"	24"
L – Length in (mm)	48.6 (1235)	44.9 (1140)	41.4 (1052)	39.2 (995)	35.7 (907)	32.3 (820)	28.8 (732)	25.3 (643)	50.8 (1290)	47.3 (1202)	45.1 (1145)	41.6 (1057)	38.2 (970)	34.7 (882)	31.2 (793)	27.8 (707)
W – Width in (mm)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)
H – Height in (mm)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)

Flange Size	DC68/DC78								DC68.1/DC78.1					DC69.5/DC79.5								
	10"	12"	14"	16"	18"	20"	22"	24"	16"	18"	20"	22"	24"	16"	18"	20"	22"	24"	26"	28"	30"	
L – Length in (mm)	57.9 (1470)	54.4 (1382)	52.2 (1325)	48.7 (1237)	45.3 (1150)	41.8 (1062)	38.3 (973)	34.9 (887)	56.7 (1439)	53.3 (1354)	49.9 (1267)	46.4 (1178)	42.9 (1090)	64.2 (1632)	60.9 (1546)	57.4 (1459)	54.0 (1370)	50.5 (1282)	46.1 (1170)	42.6 (1082)	40.2 (1021)	
W – Width in (mm)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	47.3 (1202)	47.3 (1202)	47.3 (1202)	47.3 (1202)	47.3 (1202)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)	51.7 (1313)
H – Height in (mm)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	47.8 (1213)	47.8 (1213)	47.8 (1213)	47.8 (1213)	47.8 (1213)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)	52.1 (1324)

Note: The QUICK-LID® housing is not limited to the flange sizes listed above or to symmetrical inlet/outlet configurations. Contact DCL for more information on these products.



Hole pattern complies to ANSI 150# Class Bolt Pattern Flanges