



Head office address: 241 Bradwick Drive, Concord, Ontario, Canada L4K 1K5

Mailing address: P.O. Box 90, Concord, Ontario, Canada L4K 1B2

Tel: (905) 660-6450 Toll free: 1-800-872-1968 Fax: (905) 660-6435 E-mail: info@dcl-inc.com Website: www.dcl-inc.com



QUICK-LID® HOUSINGS WITH DIN FLANGES

Flange Size (mm)	DC63/DC73					DC64/DC74						DC64.5/DC74.5					
	150	200	250	300	350	200	250	300	350	400	450	200	250	300	350	400	450
L – Length in (mm)	34.3 (871)	30.8 (782)	27.1 (688)	23.6 (599)	21.4 (543)	37.5 (954)	33.8 (858)	30.3 (770)	28.1 (713)	24.6 (626)	21.5 (546)	42.6 (1083)	38.9 (989)	35.4 (900)	33.2 (844)	29.7 (755)	26.2 (666)
W – Width in (mm)	24.9 (632)	24.9 (632)	24.9 (632)	24.9 (632)	24.9 (632)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	28.7 (729)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)	31.7 (805)
H – Height in (mm)	25.3 (642)	25.3 (642)	25.3 (642)	25.3 (642)	25.3 (642)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	29.1 (739)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)	32.1 (816)

Flange Size (mm)	DC65/DC75							DC66/DC76						
	200	250	300	350	400	450	500	250	300	350	400	450	500	600
L – Length in (mm)	48.7 (1237)	45.0 (1143)	41.5 (1054)	39.3 (998)	35.8 (909)	32.3 (820)	28.8 (732)	50.9 (1293)	47.4 (1204)	45.2 (1148)	41.7 (1059)	38.2 (970)	34.7 (882)	27.1 (689)
W – Width in (mm)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	35.2 (894)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)	38.6 (981)
H – Height in (mm)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	35.6 (905)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)	39.0 (992)

Flange Size (mm)	DC68/DC78							DC68.1/DC78.1				DC69.5/DC79.5		
	250	300	350	400	450	500	600	400	450	500	700	400	450	500
L – Length in (mm)	58.0 (1473)	54.5 (1384)	52.3 (1328)	48.8 (1239)	45.3 (1150)	41.8 (1062)	34.1 (867)	56.8 (1443)	53.3 (1353)	49.8 (1265)	35.5 (902)	64.4 (1635)	60.9 (1546)	57.4 (1457)
W – Width in (mm)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	42.7 (1085)	47.3 (1202)	47.3 (1202)	47.3 (1202)	47.3 (1202)	51.7 (1313)	51.7 (1313)	51.7 (1313)
H – Height in (mm)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	43.1 (1096)	47.8 (1213)	47.8 (1213)	47.8 (1213)	47.8 (1213)	52.1 (1324)	52.1 (1324)	52.1 (1324)

Note: The QUICK-LID® housing is not limited to the flange sizes listed above or to symmetrical inlet/outlet configurations. Contact DCL for more information on these products.



Hole pattern complies to DIN 2573 / DIN 86044 Bolt Pattern Flanges. Drilling according to other standards is available.

Last Revised: June 26, 2012
X0001-0000-72

DCL's policy is that of continuous product improvement. DCL reserves the right to change any information without notice.