



Head office address: 241 Bradwick Drive, Concord, Ontario, Canada L4K 1K5  
 Mailing address: P.O. Box 90, Concord, Ontario, Canada L4K 1B2

Tel: (905) 660-6450 Toll free: 1-800-872-1968 Fax: (905) 660-6435 E-mail: info@dcl-inc.com Website: www.dcl-inc.com



## QUICK-LID® HOUSINGS WITH ANSI FLANGES

| Flange Size           | DC63/DC73     |               |               |               | DC64/DC74     |               |               |               |               |               | DC64.5/DC74.5  |               |               |               |               |               |
|-----------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|----------------|---------------|---------------|---------------|---------------|---------------|
|                       | 6"            | 8"            | 10"           | 12"           | 8"            | 10"           | 12"           | 14"           | 16"           | 18"           | 8"             | 10"           | 12"           | 14"           | 16"           | 18"           |
| L – Length<br>in (mm) | 35.1<br>(892) | 30.7<br>(779) | 27.0<br>(685) | 23.5<br>(597) | 37.3<br>(947) | 33.6<br>(853) | 30.2<br>(768) | 27.9<br>(709) | 24.5<br>(622) | 20.2<br>(512) | 42.6<br>(1081) | 38.8<br>(986) | 35.4<br>(898) | 33.1<br>(841) | 29.6<br>(753) | 26.2<br>(666) |
| W – Width<br>in (mm)  | 24.9<br>(632) | 24.9<br>(632) | 24.9<br>(632) | 24.9<br>(632) | 28.7<br>(729) | 28.7<br>(729) | 28.7<br>(729) | 28.7<br>(729) | 28.7<br>(729) | 28.7<br>(729) | 31.7<br>(805)  | 31.7<br>(805) | 31.7<br>(805) | 31.7<br>(805) | 31.7<br>(805) | 31.7<br>(805) |
| H – Height<br>in (mm) | 25.3<br>(642) | 25.3<br>(642) | 25.3<br>(642) | 25.3<br>(642) | 29.1<br>(739) | 29.1<br>(739) | 29.1<br>(739) | 29.1<br>(739) | 29.1<br>(739) | 29.1<br>(739) | 32.1<br>(816)  | 32.1<br>(816) | 32.1<br>(816) | 32.1<br>(816) | 32.1<br>(816) | 32.1<br>(816) |

| Flange Size           | DC65/DC75      |                |                |               |               |               |               |               | DC66/DC76      |                |                |                |               |               |               |               |
|-----------------------|----------------|----------------|----------------|---------------|---------------|---------------|---------------|---------------|----------------|----------------|----------------|----------------|---------------|---------------|---------------|---------------|
|                       | 8"             | 10"            | 12"            | 14"           | 16"           | 18"           | 20"           | 22"           | 10"            | 12"            | 14"            | 16"            | 18"           | 20"           | 22"           | 24"           |
| L – Length<br>in (mm) | 48.6<br>(1235) | 44.9<br>(1140) | 41.4<br>(1052) | 39.2<br>(995) | 35.7<br>(907) | 32.3<br>(820) | 28.8<br>(732) | 25.3<br>(643) | 50.8<br>(1290) | 47.3<br>(1202) | 45.1<br>(1145) | 41.6<br>(1057) | 38.2<br>(970) | 34.7<br>(882) | 31.2<br>(793) | 27.8<br>(707) |
| W – Width<br>in (mm)  | 35.2<br>(894)  | 35.2<br>(894)  | 35.2<br>(894)  | 35.2<br>(894) | 35.2<br>(894) | 35.2<br>(894) | 35.2<br>(894) | 35.2<br>(894) | 38.6<br>(981)  | 38.6<br>(981)  | 38.6<br>(981)  | 38.6<br>(981)  | 38.6<br>(981) | 38.6<br>(981) | 38.6<br>(981) | 38.6<br>(981) |
| H – Height<br>in (mm) | 35.6<br>(905)  | 35.6<br>(905)  | 35.6<br>(905)  | 35.6<br>(905) | 35.6<br>(905) | 35.6<br>(905) | 35.6<br>(905) | 35.6<br>(905) | 39.0<br>(992)  | 39.0<br>(992)  | 39.0<br>(992)  | 39.0<br>(992)  | 39.0<br>(992) | 39.0<br>(992) | 39.0<br>(992) | 39.0<br>(992) |

| Flange Size           | DC68/DC78      |                |                |                |                |                |                |                | DC68.1/DC78.1  |                |                |                |                | DC69.5/DC79.5  |                |                |                |                |                |                |                |                |
|-----------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
|                       | 10"            | 12"            | 14"            | 16"            | 18"            | 20"            | 22"            | 24"            | 16"            | 18"            | 20"            | 22"            | 24"            | 16"            | 18"            | 20"            | 22"            | 24"            | 26"            | 28"            | 30"            |                |
| L – Length<br>in (mm) | 57.9<br>(1470) | 54.4<br>(1382) | 52.2<br>(1325) | 48.7<br>(1237) | 45.3<br>(1150) | 41.8<br>(1062) | 38.3<br>(973)  | 34.9<br>(887)  | 56.7<br>(1439) | 53.3<br>(1354) | 49.9<br>(1267) | 46.4<br>(1178) | 42.9<br>(1090) | 64.2<br>(1632) | 60.9<br>(1546) | 57.4<br>(1459) | 54.0<br>(1370) | 50.5<br>(1282) | 46.1<br>(1170) | 42.6<br>(1082) | 40.2<br>(1021) |                |
| W – Width<br>in (mm)  | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 42.7<br>(1085) | 47.3<br>(1202) | 47.3<br>(1202) | 47.3<br>(1202) | 47.3<br>(1202) | 47.3<br>(1202) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) | 51.7<br>(1313) |
| H – Height<br>in (mm) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 43.1<br>(1096) | 47.8<br>(1213) | 47.8<br>(1213) | 47.8<br>(1213) | 47.8<br>(1213) | 47.8<br>(1213) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) | 52.1<br>(1324) |

Note: The QUICK-LID® housing is not limited to the flange sizes listed above or to symmetrical inlet/outlet configurations. Contact DCL for more information on these products.



Hole pattern complies to ANSI 150# Class Bolt Pattern Flanges